

Patch cable MU - GigaPATCH™

GigaPATCH™ MU patch cable is produced in i.hht. according to the latest standards, and with the latest generation of test and production tools. 100% tested, both visually, for RL (reflection) and IL (attenuation).

- Stable and high quality
- Visual inspection with 600x magnification of 100% of connectors
- Control of the connectors Geometry, Radius, Fibre height, Apex Offset, Ferrule and Fibre Closing
- Produktion certifierad i.hht ISO9001:2002 och ISO14001:2004
- RoHS i.hht 2002/95/ES



Dimensions and characteristics

Standards		IEC 61754-6, Telcordia GR-326			
IL = Insertion loss		SM			MM
RL = Reflection loss		SPC	UPC	APC	-
Threshold	IL (dB)	<0,3	<0,3	<0,3	<0,3
Typical value	IL (dB)	0,15	0,12	0,15	0,14
Threshold	RL (dB)	>45	>50	>60	-
Typical value	RL (dB)	49	53	62	-

Ordering Information

GCU6U60115xxxGY	Patch SPX MU-MU MM 62,5/125/2000 (OM1) xM Gray LS0H
GCU5U50115xxxOR	Patch SPX MU-MU MM 50/125/2000 (OM2) xM Orange LS0H
GCU3U30115xxxAQ	Patch SPX MU-MU MM 50/125/2000 (OM3) xM Light blue LS0H
GCUUUU0115xxxYE	Patch SPX MU/UPC-MU/UPC SM 9/125/2000 (OS1) xM Yellow LS0H
GCUUAUA0115xxxYE	Patch SPX MU/APC-MU/APC SM 9/125/2000 (OS1) xM Yellow LS0H
GCU6U60215xxxGY	Patch DPX MU-MU MM 62,5/125/2000 (OM1) xM Gray LS0H
GCU5U50215xxxOR	Patch DPX MU-MU MM 50/125/2000 (OM2) xM Orange LS0H
GCU3U30215xxxAQ	Patch DPX MU-MU MM 50/125/2000 (OM3) xM Light blue LS0H
GCUUUU0215xxxYE	Patch DPX MU/UPC-MU/UPC SM 9/125/2000 (OS1) xM Yellow LS0H
GCUUAUA-0215xxxYE	Patch DPX MU/APC-MU/APC SM 9/125/2000 (OS1) xM Yellow LS0H

xxx: Length in meter. (C50=0,5M, 001=1M, 1M5=1,5M, 005=5M, 010=10M, 100=100M)

GigaCom reserves the right to make changes in this specification without prior notice.