

Patch cable SC - GigaPATCH™

GigaPATCH™ SC patch cable is produced in i.hht. according to the latest standards, and with the latest generation of test and production tools.
100% tested, both visually, for RL (reflection) and IL (attenuation).



- Stable and high quality
- Visual inspection with 600x magnification of 100% of connectors
- Control of the connectors Geometry, Radius, Fibre height, Apex Offset, Ferrule and Fibre Closing
- The contacts are color coded i.hht IEC 60874-19
Beige for MM, Blue for SM and Green for APC
- Produktion certifierad i.hht ISO9001:2002 och
ISO14001:2004
- RoHS i.hht 2002/95/ES

Dimensions and characteristics

Standards		IEC 61754-4, Telcordia GR-326, EN 50173-1:2000			
IL = Insertion loss		SM			MM
RL = Reflection loss		SPC	UPC	APC	-
Threshold	IL (dB)	<0,3	<0,3	<0,3	<0,3
Typical value	IL (dB)	0,15	0,12	0,15	0,14
Threshold	RL (dB)	>45	>50	>60	-
Typical value	RL (dB)	49	53	62	-

Ordering Information

GCS6S60115xxxGY	Patch SPX SC-SC MM 62,5/125/2000 (OM1) xM Gray LS0H
GCS5S50115xxxOR	Patch SPX SC-SC MM 50/125/2000 (OM2) xM Orange LS0H
GCS3S30115xxxAQ	Patch SPX SC-SC MM 50/125/2000 (OM3) xM Light blue LS0H
GCSUSU0115xxxYE	Patch SPX SC/UPC-SC/UPC SM 9/125/2000 (OS1) xM Yellow LS0H
GCSASA0115xxxYE	Patch SPX SC/APC-SC/APC SM 9/125/2000 (OS1) xM Yellow LS0H
GCS6V60215xxxGY	Patch DPX SC-SCD MM 62,5/125/2000 (OM1) xM Gray LS0H
GCS5V50215xxxOR	Patch DPX SC-SCD MM 50/125/2000 (OM2) xM Orange LS0H
GCS3V30215xxxAQ	Patch DPX SC-SCD MM 50/125/2000 (OM3) xM Light blue LS0H
GCSUVU0215xxxYE	Patch DPX SC/UPC-SCD/UPC SM 9/125/2000 (OS1) xM Yellow LS0H
GCSAVA0215xxxYE	Patch DPX SC/APC-SCD/APC SM 9/125/2000 (OS1) xM Yellow LS0H

xxx: Length in meter. (C50=0,5M, 001=1M, 1M5=1,5M, 005=5M, 010=10M, 100=100M)

DPX: One is the clipped, other open (clips included in the bag)

GigaCom reserves the right to make changes in this specification without prior notice.