

Patch cable hybrid SC-ST GigaPATCH™

GigaPATCH™ SC-ST patch cable is produced in i.hht. according to the latest standards, and with the latest generation of test and production tools. 100% tested, both visually, for RL (reflection) and IL (attenuation).



- Stable and high quality
- Visual inspection with 600x magnification of 100% of connectors
- Control of the connectors Geometry, Radius, Fibre height, Apex Offset, Ferrule and Fibre Closing
- The contacts are color coded i.hht IEC 60874-19 Beige for MM, Blue for SM and Green for APC
- Produktion certifierad i.hht ISO9001:2002 och ISO14001:2004
- RoHS i.hht 2002/95/ES

Dimensions and characteristics

Standards		IEC 61754-2, IEC 61754-4, Telcordia GR-326		
IL = Insertion loss RL = Reflection loss		SM		MM
		SPC	UPC	-
Threshold	IL (dB)	<0,3	<0,3	<0,3
Typical value	IL (dB)	0,15	0,12	0,14
Threshold	RL (dB)	>45	>50	-
Typical value	RL (dB)	49	53	-

Ordering Information

GCS6T60115xxxGY	Patch SPX SC-ST MM 62,5/125/2000 (OM1) xM Gray LSOH
GCS5T50115xxxOR	Patch SPX SC-ST MM 50/125/2000 (OM2) xM Orange LSOH
GCS3T30115xxxAQ	Patch SPX SC-ST MM 50/125/2000 (OM3) xM Light blue LSOH
GCS5T50115xxxYE	Patch SPX SC/UPC-ST/UPC SM 9/125/2000 (OS1) xM Yellow LSOH
GCT6V60215xxxGY	Patch DPX SCD-ST MM 62,5/125/2000 (OM1) xM Gray LSOH
GCT5V50215xxxOR	Patch DPX SCD-ST MM 50/125/2000 (OM2) xM Orange LSOH
GCT3V30215xxxAQ	Patch DPX SCD-ST MM 50/125/2000 (OM3) xM Light blue LSOH
GCTUVU0215xxxYE	Patch DPX SCD/UPC-ST/UPC SM 9/125/2000 (OS1) xM Yellow LSOH

xxx: Length in meter. (C50=0,5M, 001=1M, 1M5=1,5M, 005=5M, 010=10M, 100=100M)

DPX: LC clipped tougher, SC open (clips included in the bag)

GigaCom reserves the right to make changes in this specification without prior notice.